



Department of Public Works
Engineering Division
 Kathy Cryan, Interim Engineering Manager
 City-County Building, Room 115
 210 Martin Luther King, Jr. Boulevard
 Madison, Wisconsin 53703
 Phone: (608) 266-4751
 Fax: (608) 264-9275
engineering@cityofmadison.com
www.cityofmadison.com/engineering

Deputy City Engineer
 Gregory T. Fries, P.E.
Principal Architect 2
 Bryan Cooper, AIA
Principal Engineer 2
 John S. Fahrney, P.E.
 Chris Petykowski, P.E.
 Janet Schmidt, P.E.
Principal Engineer 1
 Christina M. Bachmann, P.E.
 Mark D. Moder, P.E.
 James M. Wolfe, P.E.
Financial Manager
 Steven B. Danner-Rivers

July 6, 2022

**NOTICE OF ADDENDUM
 ADDENDUM NO. 1
 CONTRACT NO. 9107**

CIPP UV LINING REHAB OF SANITARY SEWERS - 2022

Revise and amend the contract document(s) for the above project as stated in this addendum, otherwise, the original document shall remain in effect.

SPECIFICATIONS:

SECTION A: ADVERTISEMENT FOR BIDS AND INSTRUCTIONS TO BIDDERS

REMOVE TABLE IN ORIGINAL AND REPLACE WITH FOLLOWING TABLE:

PROJECT NAME:	CIPP UV LINING REHAB OF SANITARY SEWERS - 2022
CONTRACT NO.:	9107
SBE GOAL	3%
BID BOND	5%
SBE PRE BID MEETING	See Pre Bid Meeting info below
PREQUALIFICATION APPLICATION DUE (2:00 P.M.)	7/14/2022
BID SUBMISSION (2:00 P.M.)	8/4/2022
BID OPEN (2:30 P.M.)	8/4/2022
PUBLISHED IN WSJ	6/23/2022, 6/30/2022, 7/7/2022, 7/14/2022, 7/21/2022

SECTION D: SPECIAL PROVISIONS

REMOVE SECTION 102.1 AND REPLACE WITH THE FOLLOWING SECTION 102.1

SECTION 102.1 PRE-QUALIFICATION OF BIDDERS

CATEGORY #399 UV SEWER LINING

UV CIPP sewer lining construction requires specific and extensive knowledge and experience in UV light cured sewer lining. A resume of qualifications shall be submitted to determine if the Contractor performing the work will be prequalified under prequalification item #399, UV Sewer Lining.

The Contractor performing the work shall submit documentation demonstrating that they clearly meet the minimum qualifications as stated below:

- Contractor must show that they have a minimum of 40,000 linear feet of UV cured CIPP sewer lining successfully installed using the same UV CIPP lining system that will be used for this contract. The 40,000 linear feet shall be installed in sanitary sewer gravity mains of various sizes only, any UV CIPP installed in water main shall not apply.
- Contractor must show that the Contractor project supervisor or foreperson that will be overseeing the installation crew must have a minimum of 30,000 linear feet of UV cured CIPP sewer lining successfully installed using the same UV CIPP lining system that will be used for this contract. The 30,000 linear feet shall

