

## Traffic Engineering and Parking Divisions

David C. Dryer, P.E., City Traffic Engineer and Parking Manager

r Suite 100 215 Martin Luther King, Jr. Boulevard P.O. Box 2986 Madison, Wisconsin 53701-2986 PH 608 266 4761 TTY 866-704-2315 FAX 608 267 1158

July 21,2005 Rev: November 22, 2006

TO: Plan Commission

FROM: David C. Dryer, P.E., City Traffic Engineer and Parking Manager

## SUBJECT: 6001 Canyon Parkway – Conditional Use – 32 Condominium Units

The City Traffic Engineering Division has reviewed the subject development and has the following comments.

**MAJOR OR NON-STANDARD REVIEW COMMENTS** (Comments which are special to the project and/or may require additional work beyond a standard, more routine project.)

1. None

## PEDESTRIAN AND BICYCLE TRANSPORTATION REVIEW COMMENTS

2. None

## **GENERAL OR STANDARD REVIEW COMMENTS**

In addition, we offer the following General or Standard Review Comments:

- 3. When the applicant submits final plans for approval, the applicant shall show the following: items in the terrace as existing (e.g., signs and street light poles), type of surfaces, existing property lines, addresses, one contiguous plan (showing all easements, all pavement markings, building placement, and stalls), adjacent driveway approaches to lots on either side and across the street, signage, percent of slope, vehicle routes, dimensions of radii, aisles, driveways, stalls including the two (2) feet overhang, and a scaled drawing at 1" = 40'.
- 4. The driveway to the front of the building from the parking lot and street shall be modified to provide for two-way operation at a minimum width of eighteen ft. in accordance to M.G.O. 10.08(6)(a) 4 and noted on the plan sheets.
- 5. All directional/regulatory signage and pavement markings on the site shall be shown and

noted on the plan.

- 6. The intersection shall be so designed so as not to violate the City's sight-triangle preservations requirement which states that on a corner lot no structure, screening, or embankment of any kind shall be erected, placed, maintained or grown between the heights of 30 inches and 10 feet above the curb level or its equivalent within the triangle space formed by the two intersecting street lines or their projections and a line joining points on such street lines located a minimum of 25 feet from the street intersection in order to provide adequate vehicular vision clearance.
- 7. Public signing and marking related to the development may be required by the City Traffic Engineer for which the developer shall be financially responsible.

Please contact John Leach, City Traffic Engineering at 267-8755 if you have questions regarding the above items:

Contact Person: Aaron Otto Fax: 826-0530 Email: aott@vierbicher.com

DCD: DJM: dm