

Legend

 Denotes Boring Location



Scale: Reduced

Notes

1. Soil Borings performed by Badger State Drilling in November 2021
2. Boring locations are approximate



Date:
11/2021

Job No.
C21051-21

**Soil Boring Location Map
Hammersley Road
Madison, WI**



LOG OF TEST BORING

Project Hammersley Road
460'E of Rae, 10'N of Centerline
 Location Madison, WI

Boring No. 1
 Surface Elevation (ft) 1062±
 Job No. C21051-21
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	TYPE (in.)	Rec (in.)	Moist	N		Depth (ft)	qu (qa) (tsf)	W	LL	PL
					X	4 in. Asphalt Pavement/8 in. Base Coarse				
1	8	M	34			Medium Dense to Very Dense, Brown Fine to Medium SAND, Some Silt and Gravel, Scattered Cobbles and Boulders (SM)				
2	6	M	12							
3	8	M	61/10"							
4	18	M	14			Medium Dense, Light Brown Fine SAND, Some Gravel, Little to Some Silt (SP-SM/SM)				
5	18	M	25							
6	18	M	27							
						End Boring at 15 ft				
						Borehole backfilled with bentonite chips and asphalt patch				

WATER LEVEL OBSERVATIONS	GENERAL NOTES
While Drilling <u>∇</u> <u>NW</u> Upon Completion of Drilling _____ Time After Drilling _____ Depth to Water _____ Depth to Cave in _____	Start <u>11/17/21</u> End <u>11/17/21</u> Driller <u>BSD</u> Chief <u>KD</u> Rig <u>D-120</u> Logger <u>GB</u> Editor <u>ESF</u> Drill Method <u>2.25" HSA; Autohammer</u>
The stratification lines represent the approximate boundary between soil types and the transition may be gradual.	



LOG OF TEST BORING

Project Hammersley Road
950'W of Whitney, 15'S of Centerline
 Location Madison, WI

Boring No. 2
 Surface Elevation (ft) 1030±
 Job No. C21051-21
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES					
No.	TYPE E	Rec (in.)	Moist	N		Depth (ft)	qu (qa) (tsf)	W	LL	PL	LI
					5	X	4 in. Asphalt Pavement/8 in. Base Course				
1	█	12	M	24	5	█	Medium Dense to Dense, Brown Fine to Medium SAND, Some Silt and Gravel, Scattered Cobbles and Boulders (SM - Possible Fill to 3')				
2	█	18	M	18	5	█					
3	█	1	M	31	5	█					
4	█	1	M	41	10	█	Dense, Light Brown Fine SAND, Some Gravel, Little to Some Silt (SP-SM/SM)				
5	█	18	M	65/9"	10	█	Very Dense, Brown Silty Fine SAND, Some Gravel, Scattered Cobbles and Boulders (SM)				
6	█	14	M	98/8"	15	█					
End Boring at 15 ft											
Borehole backfilled with bentonite chips and asphalt patch											

WATER LEVEL OBSERVATIONS					GENERAL NOTES				
While Drilling	∇	NW	Upon Completion of Drilling	_____	Start	11/17/21	End	11/17/21	
Time After Drilling	_____	_____		_____	Driller	BSD	Chief	KD	Rig D-120
Depth to Water	_____	_____		_____	Logger	GB	Editor	ESF	
Depth to Cave in	_____	_____		_____	Drill Method	2.25" HSA; Autohammer			
The stratification lines represent the approximate boundary between soil types and the transition may be gradual.									



LOG OF TEST BORING

Project Hammersley Road
460'E of Whitney, 15'S of Centerline
 Location Madison, WI

Boring No. 3
 Surface Elevation (ft) 1044±
 Job No. C21051-21
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	Rec (in.)	Moist	N	Depth (ft)		q _u (tsf)	W	LL	PL	LI
				0	X	4 in. Asphalt Pavement/7 in. Base Course				
1	14	M	10	10	.	Loose to Medium Dense, Brown Fine to Medium SAND, Some Silt and Gravel, Scattered Cobbles and Boulders (SM - Possible Fill to 3')				
2	12	M	27	27	.					
3	0			50/1"	5	Very Dense, Grayish-Brown Fine to Coarse SAND and GRAVEL with Numerous Cobbles and Variable Silt Content (SP-SM/GP-GM)				
4	0			50/2"	10					
5	6	M		90/7"	15					
6	2	M		50/3"	20					
End Boring at 15 ft										
Borehole backfilled with bentonite chips and asphalt patch										

WATER LEVEL OBSERVATIONS	GENERAL NOTES
While Drilling <input checked="" type="checkbox"/> NW Upon Completion of Drilling _____ Time After Drilling _____ Depth to Water _____ Depth to Cave in _____	Start <u>11/17/21</u> End <u>11/17/21</u> Driller <u>BSD</u> Chief <u>KD</u> Rig <u>D-120</u> Logger <u>GB</u> Editor <u>ESF</u> Drill Method <u>2.25" HSA; Autohammer</u>
The stratification lines represent the approximate boundary between soil types and the transition may be gradual.	



LOG OF TEST BORING

Project Hammersley Road
850'E of Gilbert, 15'S of Centerline
 Location Madison, WI

Boring No. 4
 Surface Elevation (ft) 1037±
 Job No. C21051-21
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	TYPE E	Rec (in.)	Moist	N		Depth (ft)	q _u (qa) (tsf)	W	LL	PL
					5	4 in. Asphalt Pavement/8 in. Base Course				
1		18	M	9	5	FILL: Stiff Brown Sandy Clay				
2		18	M	49	5	Dense to Very Dense, Brown Fine to Medium SAND, Some Silt and Gravel, Scattered Cobbles and Boulders (SM)				
3		18	M	41	5					
4		18	M	37	10					
5		18	M	53	10					
6		18	M	39	15					
					15	End Boring at 15 ft Borehole backfilled with bentonite chips and asphalt patch				
					20					

WATER LEVEL OBSERVATIONS	GENERAL NOTES
While Drilling <input checked="" type="checkbox"/> NW Upon Completion of Drilling _____ Time After Drilling _____ Depth to Water _____ Depth to Cave in _____	Start <u>11/17/21</u> End <u>11/17/21</u> Driller <u>BSD</u> Chief <u>KD</u> Rig <u>D-120</u> Logger <u>GB</u> Editor <u>ESF</u> Drill Method <u>2.25" HSA; Autohammer</u>
The stratification lines represent the approximate boundary between soil types and the transition may be gradual.	



LOG OF TEST BORING

Project Hammersley Road
420'W of Reetz, 15'S of Centerline
 Location Madison, WI

Boring No. 5
 Surface Elevation (ft) 1029±
 Job No. C21051-21
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	Rec (in.)	Moist	N	Depth (ft)		q _u (qa) (tsf)	W	LL	PL	LI
				0	X	4 in. Asphalt Pavement/8 in. Base Course				
1	18	M	20	20		Medium Dense, Brown Fine to Medium SAND, Some Silt and Gravel, Scattered Cobbles and Boulders (SM)				
2	18	M	17	17						
3	8	M	27	27						
4	18	M	27	27						
				10.5						
					10.5	End Boring at 10.5 ft Due to Auger Refusal on Presumed Boulder/Possible Bedrock. Borehole backfilled with bentonite chips and asphalt patch				
				15						
				20						

WATER LEVEL OBSERVATIONS	GENERAL NOTES
While Drilling <input checked="" type="checkbox"/> NW Upon Completion of Drilling _____ Time After Drilling _____ Depth to Water _____ Depth to Cave in _____	Start <u>11/17/21</u> End <u>11/17/21</u> Driller <u>BSD</u> Chief <u>KD</u> Rig <u>D-120</u> Logger <u>GB</u> Editor <u>ESF</u> Drill Method <u>2.25" HSA; Autohammer</u>
The stratification lines represent the approximate boundary between soil types and the transition may be gradual.	

LOG OF TEST BORING
General Notes

DESCRIPTIVE SOIL CLASSIFICATION

Grain Size Terminology

Soil Fraction	Particle Size	U.S. Standard Sieve Size
Boulders	Larger than 12"	Larger than 12"
Cobbles	3" to 12"	3" to 12"
Gravel: Coarse.....	¾" to 3"	¾" to 3"
Fine	4.76 mm to ¾"	#4 to ¾"
Sand: Coarse.....	2.00 mm to 4.76 mm.....	#10 to #4
Medium	0.42 to mm to 2.00 mm	#40 to #10
Fine	0.074 mm to 0.42 mm.....	#200 to #40
Silt.....	0.005 mm to 0.074 mm.....	Smaller than #200
Clay.....	Smaller than 0.005 mm.....	Smaller than #200

Plasticity characteristics differentiate between silt and clay.

General Terminology

- Physical Characteristics
Color, moisture, grain shape, fineness, etc.
- Major Constituents
Clay, silt, sand, gravel
- Structure
Laminated, varved, fibrous, stratified, cemented, fissured, etc.
- Geologic Origin
Glacial, alluvial, eolian, residual, etc.

Relative Density

Term	"N" Value
Very Loose.....	0 - 4
Loose.....	4 - 10
Medium Dense.....	10 - 30
Dense.....	30 - 50
Very Dense.....	Over 50

Relative Proportions Of Cohesionless Soils

Proportional Term	Defining Range by Percentage of Weight
Trace.....	0% - 5%
Little.....	5% - 12%
Some.....	12% - 35%
And	35% - 50%

Consistency

Term	q _v -tons/sq. ft
Very Soft.....	0.0 to 0.25
Soft.....	0.25 to 0.50
Medium.....	0.50 to 1.0
Stiff.....	1.0 to 2.0
Very Stiff.....	2.0 to 4.0
Hard.....	Over 4.0

Organic Content by Combustion Method

Soil Description	Loss on Ignition
Non Organic.....	Less than 4%
Organic Silt/Clay.....	4 - 12%
Sedimentary Peat.....	12% - 50%
Fibrous and Woody Peat...	More than 50%

Plasticity

Term	Plastic Index
None to Slight.....	0 - 4
Slight.....	5 - 7
Medium.....	8 - 22
High to Very High ..	Over 22

The penetration resistance, N, is the summation of the number of blows required to effect two successive 6" penetrations of the 2" split-barrel sampler. The sampler is driven with a 140 lb. weight falling 30" and is seated to a depth of 6" before commencing the standard penetration test.

SYMBOLS

Drilling and Sampling

- CS – Continuous Sampling
- RC – Rock Coring: Size AW, BW, NW, 2"W
- RQD – Rock Quality Designation
- RB – Rock Bit/Roller Bit
- FT – Fish Tail
- DC – Drove Casing
- C – Casing: Size 2 ½", NW, 4", HW
- CW – Clear Water
- DM – Drilling Mud
- HSA – Hollow Stem Auger
- FA – Flight Auger
- HA – Hand Auger
- COA – Clean-Out Auger
- SS - 2" Dia. Split-Barrel Sample
- 2ST – 2" Dia. Thin-Walled Tube Sample
- 3ST – 3" Dia. Thin-Walled Tube Sample
- PT – 3" Dia. Piston Tube Sample
- AS – Auger Sample
- WS – Wash Sample
- PTS – Peat Sample
- PS – Pitcher Sample
- NR – No Recovery
- S – Sounding
- PMT – Borehole Pressuremeter Test
- VS – Vane Shear Test
- WPT – Water Pressure Test

Laboratory Tests

- q_a – Penetrometer Reading, tons/sq ft
- q_a – Unconfined Strength, tons/sq ft
- W – Moisture Content, %
- LL – Liquid Limit, %
- PL – Plastic Limit, %
- SL – Shrinkage Limit, %
- LI – Loss on Ignition
- D – Dry Unit Weight, lbs/cu ft
- pH – Measure of Soil Alkalinity or Acidity
- FS – Free Swell, %

Water Level Measurement

- ▽ - Water Level at Time Shown
- NW – No Water Encountered
- WD – While Drilling
- BCR – Before Casing Removal
- ACR – After Casing Removal
- CW – Cave and Wet
- CM – Caved and Moist
















Note: Water level measurements shown on the boring logs represent conditions at the time indicated and may not reflect static levels, especially in cohesive soils.

CGC, Inc.

Madison - Milwaukee

Unified Soil Classification System

UNIFIED SOIL CLASSIFICATION AND SYMBOL CHART

COARSE-GRAINED SOILS (more than 50% of material is larger than No. 200 sieve size)		
Clean Gravels (Less than 5% fines)		
GRAVELS More than 50% of coarse fraction larger than No. 4 sieve size	 GW Well-graded gravels, gravel-sand mixtures, little or no fines	
	 GP Poorly-graded gravels, gravel-sand mixtures, little or no fines	
	Gravels with fines (More than 12% fines)	
	 GM Silty gravels, gravel-sand-silt mixtures	
 GC Clayey gravels, gravel-sand-clay mixtures		
Clean Sands (Less than 5% fines)		
SANDS 50% or more of coarse fraction smaller than No. 4 sieve size	 SW Well-graded sands, gravelly sands, little or no fines	
	 SP Poorly graded sands, gravelly sands, little or no fines	
	Sands with fines (More than 12% fines)	
	 SM Silty sands, sand-silt mixtures	
 SC Clayey sands, sand-clay mixtures		
FINE-GRAINED SOILS (50% or more of material is smaller than No. 200 sieve size.)		
SILTS AND CLAYS Liquid limit less than 50%	 ML Inorganic silts and very fine sands, rock flour, silty or clayey fine sands or clayey silts with slight plasticity	
	 CL Inorganic clays of low to medium plasticity, gravelly clays, sandy clays, silty clays, lean clays	
	 OL Organic silts and organic silty clays of low plasticity	
SILTS AND CLAYS Liquid limit 50% or greater	 MH Inorganic silts, micaceous or diatomaceous fine sandy or silty soils, elastic silts	
	 CH Inorganic clays of high plasticity, fat clays	
	 OH Organic clays of medium to high plasticity, organic silts	
HIGHLY ORGANIC SOILS	 PT Peat and other highly organic soils	

LABORATORY CLASSIFICATION CRITERIA

GW	$C_u = \frac{D_{60}}{D_{10}}$ greater than 4; $C_c = \frac{D_{30}}{D_{10} \times D_{60}}$ between 1 and 3	
GP	Not meeting all gradation requirements for GW	
GM	Atterberg limits below "A" line or P.I. less than 4	Above "A" line with P.I. between 4 and 7 are borderline cases requiring use of dual symbols
GC	Atterberg limits above "A" line or P.I. greater than 7	
SW	$C_u = \frac{D_{60}}{D_{10}}$ greater than 4; $C_c = \frac{D_{30}}{D_{10} \times D_{60}}$ between 1 and 3	
SP	Not meeting all gradation requirements for GW	
SM	Atterberg limits below "A" line or P.I. less than 4	Limits plotting in shaded zone with P.I. between 4 and 7 are borderline cases requiring use of dual symbols
SC	Atterberg limits above "A" line with P.I. greater than 7	

Determine percentages of sand and gravel from grain-size curve. Depending on percentage of fines (fraction smaller than No. 200 sieve size), coarse-grained soils are classified as follows:

Less than 5 percent GW, GP, SW, SP
 More than 12 percent GM, GC, SM, SC
 5 to 12 percent Borderline cases requiring dual symbols

PLASTICITY CHART

