

Legend


 Denotes Boring Location



Notes

1. Soil borings performed by America's Drilling Co. in October 2022
2. Boring locations are approximate

Scale: Reduced

Date: 10/2022	
Job No. C22051-20	

Soil Boring Location Map
Schmitt Pl & Harvey St
Madison, WI



LOG OF TEST BORING

Project Schmitt Place and Harvey Street
Schmitt: 170'N of Harvey, 5'E of Centerline
 Location Madison, Wisconsin

Boring No. 1
 Surface Elevation (ft) 896±
 Job No. C22051-20
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	TYPE	Rec (in.)	Moist	N		Depth (ft)	qu (qa) (tsf)	W	LL	PL
					5 in. Asphalt Pavement/7 in. Base Course					
1AS		0	M	7	FILL: Loose Brown Sand with Silt, Gravel and Clay					
					Stiff, Brown Lean CLAY (CL)					
2		10	M	8		(1.75)				
					Becoming sandy and very soft near 6 ft					
3		12	M	4		(0.5-0.25)				
					Apparent Weathered to Competent Sandy Dolomitic Limestone Bedrock					
4		1	M	50/2"	Hard drilling beginning at 8 ft					
					End of Boring at 9 ft Due to Auger Refusal on Apparent Bedrock					
					Backfilled with bentonite chips and asphalt patch					

WATER LEVEL OBSERVATIONS

GENERAL NOTES

While Drilling ∇ NW Upon Completion of Drilling _____
 Time After Drilling _____
 Depth to Water _____
 Depth to Cave in _____

Start 10/6/22 End 10/6/22
 Driller ADC Chief KD Rig CME-55
 Logger DB Editor ESF
 Drill Method 2.25" HSA; Autohammer

The stratification lines represent the approximate boundary between soil types and the transition may be gradual.



LOG OF TEST BORING

Project Schmitt Place and Harvey Street
Schmitt: 165'N of Harvey, 5'E of Centerline
 Location Madison, Wisconsin

Boring No. 1X
 Surface Elevation (ft) 896±
 Job No. C22051-20
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES					
No.	TYPE	Rec (in.)	Moist	N		Depth (ft)	qu (qa) (tsf)	W	LL	PL	LOI
					5	X X					
						5 in. Asphalt Pavement/7 in. Base Course					
						Blind drill to 9 ft See B1 for soils information					
						Hard drilling beginning at 8 ft					
					10	End of Boring at 9 ft Due to Auger Refusal on Apparent Bedrock					
						Backfilled with bentonite chips and asphalt patch					
					15						

WATER LEVEL OBSERVATIONS

GENERAL NOTES

While Drilling ∇ NW Upon Completion of Drilling _____
 Time After Drilling _____
 Depth to Water _____
 Depth to Cave in _____

Start 10/6/22 End 10/6/22
 Driller ADC Chief KD Rig CME-55
 Logger DB Editor ESF
 Drill Method 2.25" HSA; Autohammer

The stratification lines represent the approximate boundary between soil types and the transition may be gradual.



LOG OF TEST BORING

Project Schmitt Place and Harvey Street
Harvey: 375'E of Schmitt, 5'S of Centerline
 Location Madison, Wisconsin

Boring No. 2
 Surface Elevation (ft) 895±
 Job No. C22051-20
 Sheet 1 of 1

2921 Perry Street, Madison, WI 53713 (608) 288-4100, FAX (608) 288-7887

SAMPLE					VISUAL CLASSIFICATION and Remarks	SOIL PROPERTIES				
No.	TYPE	Rec (in.)	Moist	N		Depth (ft)	q _u (qa) (tsf)	W	LL	PL
					0	4 in. Asphalt Pavement/7 in. Base Course				
1		10	M	8	8	Loose, Brown SILT (ML)				
2		10	M	10	10	Very Stiff, Brown Lean CLAY (CL)				
3		12	M	5	12	Becoming medium-stiff and sandy near 6 ft				
4		14	M	23	14	Medium Dense, Brown Fine to Coarse SAND and GRAVEL, Some Silt (SM/GM)				
5		0	-	50/2"	10.5	Apparent Bedrock Hard drilling beginning at 10.5 ft				
6		0	-	50/0"	13	End of Boring at 13 ft Due to Auger Refusal on Apparent Bedrock				
					15	Backfilled with bentonite chips and asphalt patch				

WATER LEVEL OBSERVATIONS

GENERAL NOTES

While Drilling NW Upon Completion of Drilling _____
 Time After Drilling _____
 Depth to Water _____
 Depth to Cave in _____

Start 10/6/22 End 10/6/22
 Driller ADC Chief KD Rig CME-55
 Logger DB Editor ESF
 Drill Method 2.25" HSA; Autohammer

The stratification lines represent the approximate boundary between soil types and the transition may be gradual.