



TERMINATE 10' BEYOND PROPERTY LINE UNLESS SPECIFIED

RECORD DISTANCE TO A PROPERTY CORNER (IRON) FOR EACH LATERAL

CENTERLINE OF ZERO LOT LINE DUPLEX LOT

5' 5'

10' 0+36

0+74

1+46

0+26

0+76

1+44

LATERALS INSTALLED PERPENDICULAR TO SANITARY SEWER MAIN (TYPICAL)

RECORD THE STATION DISTANCE FROM CENTER OF SAS TO CENTER OF WYE

4"X4" TIMBER 8' LONG SHALL EXTEND FROM END OF LATERAL TO 1' ABOVE FINISHED GRADE

STUB

0+84

0+46

1+09

0+82

0+51

TERMINATE AT PROPERTY LINE ON CUL-DE-SACS WITHOUT SIDEWALKS (10' WITH SIDEWALKS UNLESS SPECIFIED)

INSTALL LATERAL OUT OF SAS AT ALIGNMENT SHOWN ON PLANS, OR AS DIRECTED BY THE ENGINEER. PROVIDE FLEXIBLE PIPE TO SAS CONNECTOR FOR LATERAL PER SDD 5.7.31

WHERE "X", THE DISTANCE BETWEEN THE LATERAL AND THE PROPERTY DOWNSTREAM, EQUALS

2006

LOT WIDTH -10'
2

CITY OF MADISON
ENGINEERING DIVISION

LOCATION OF
SANITARY LATERALS

STANDARD DETAIL DRAWING 5.3.2

NOTE:
ALL SANITARY SEWER LATERALS SHALL INCLUDE SANITARY LATERAL MARKER DISKS ABOVE THE LATERAL AT THE WYE & AT THE PROPERTY LINE.

UNLESS OTHERWISE SPECIFIED ON THE PLAN OR DIRECTED BY THE ENGINEER